



Main

Range	Acti 9
Product or component type	Overvoltage protection auxiliary (2 circuits)
Device short name	iACTp
[Uc] control circuit voltage	12...48 V AC 50/60 Hz

Complementary

Type of setting	Time delay configuration
Time delay range	1...36000 s
Hold-in power consumption in VA	3 VA
Mounting mode	Fixed, on the left of CT
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Colour	White
Overvoltage category	III
[Uimp] rated impulse withstand voltage	4 kV
[Ui] rated insulation voltage	440 V
Standards	IEC/EN 61095
Connections - terminals	Control circuit: tunnel type terminals 2 cable(s) 2.5 mm ² flexible Control circuit: tunnel type terminals 2 cable(s) 1.5 mm ² rigid Control circuit: tunnel type terminals 1 cable(s) 1.5...2.5 mm ² rigid Control circuit: tunnel type terminals 1 cable(s) 1.5...2.5 mm ² flexible with ferrule Control circuit: yellow clips
Wire stripping length	9 mm
Tightening torque	0.8 N.m
Range compatibility	Acti9 iCT
Market segment	Residential Small commercial
Compatibility code	iACTp

Environment

IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-5...50 °C
Ambient air temperature for storage	40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	56 g
Package 1 Height	1.8 cm
Package 1 width	6.7 cm
Package 1 Length	8.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	727 g
Package 2 Height	10 cm
Package 2 width	8 cm
Package 2 Length	23 cm
Unit Type of Package 3	S03
Number of Units in Package 3	48
Package 3 Weight	3.395 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts & cables product

Contractual warranty

Warranty	18 months
----------	-----------