



Main

Range	TeSys
Product name	TeSys Mini-VARIO
Device short name	VCCDN
Product or component type	Emergency stop switch disconnecter
Performance level	Standard
Poles description	3P
Contacts type and composition	3 NO
Network type	AC DC
Control type	Rotary handle
Rotary handle mounting style	Extended
Handle colour	Red
Handle front plate colour	Yellow
Rotary handle padlocking	1 to 3 padlocks 4...8 mm

Complementary

Marking	0 - 1
Mounting support	Handle: door Switch: symmetrical rail
Fixing mode	Hole with 22.5 mm for handle By clips for switch
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	12 A
[Ithe] conventional enclosed thermal current	10 A
[Ie] rated operational current	8.1 A (AC-23) at 400 V
Rated operational power in W	3 kW at 230...240 V (AC-23A) 4 kW at 400...415 V (AC-23A) 5.5 kW at 500 V (AC-23A) 7.5 kW at 690 V (AC-23A) 1.5 kW at 230...240 V (AC-3) 3 kW at 400...415 V (AC-3) 4 kW at 500 V (AC-3) 4 kW at 690 V (AC-3)
Intermittent duty class	30
Making capacity (I Rms)	120 A at 400 V AC-21A 120 A at 400 V AC-22A 120 A at 400 V AC-23A
[Icm] rated short-circuit making capacity	0.5 kA at 400 V at Ipeak
[Icw] rated short-time withstand Rms current	140 A at 400 V duration: 1 s
Rated conditional short-circuit current	6 kA at 400 V - associated fuse 12 A aM 6 kA at 400 V - associated fuse 12 A gG
Breaking capacity	120 kA at 400 V (AC-21A) 120 kA at 400 V (AC-22A) 120 kA at 400 V (AC-23A)
Device composition	Switch Handle Shaft extension

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mechanical durability	50000 cycles
Electrical durability	30000 Cycles DC-1...5 50000 cycles AC-21
Suitability for isolation	Yes
Connections - terminals	Power circuit: screw clamp terminals 4 mm ² - flexible - with cable end Power circuit: screw clamp terminals 4 mm ² - solid
Tightening torque	Power circuit: 0.7 N.m - on screw clamp terminals
Handle front plate dimension	60 x 60 mm
Height	60 mm
Width	60 mm
Net weight	0.334 kg

Environment

Standards	IEC 60947-3
Product certifications	GL CCC UL CSA
Protective treatment	TC
IP degree of protection	IP65
Mechanical robustness	Vibrations 10...150 Hz (5 gn) conforming to IEC 60068-2-6 Shocks 11 ms (15 gn) conforming to IEC 60068-2-27
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	314 g
Package 1 Height	7.5 cm
Package 1 width	8.8 cm
Package 1 Length	25.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Weight	4.282 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------