



Main

Range	TeSys
Product Name	TeSys VARIO
Device Short Name	V
Product Type	Switch body

Complementary

Mounting Support	Symmetrical rail Plate
Performance Level	High performance
Number of Poles	3P
Contact Type and Composition	3 NO
Network type	AC DC
Network frequency	50/60 Hz
[Ue] IEC Rated Operational Voltage	690 V AC 50/60 Hz
IEC Rated Operational Power in W	30 KW at 230...240 V (AC-3) 37 KW at 400...415 V (AC-3) 37 KW at 690 V (AC-3) 45 KW at 500 V (AC-3) 45 KW at 690 V (AC-23A) 55 KW at 500 V (AC-23A) 30 KW at 230...240 V (AC-23A) 45 kW at 400...415 V (AC-23A)
[Ie] Rated Operational Current	83 A AC-23 Ue: 400 V
[Ith] Conventional Free Air Thermal Current	175 A
[Ithe] Conventional Enclosed Thermal Current	140 A
Making capacity (I Rms)	1750 A at 400 V AC-22A 1750 A at 400 V AC-23A 1600 A at 400 V AC-21A
Breaking Capacity	1400 A at 400 V (AC-21A) 1400 A at 400 V (AC-22A) 1400 A at 400 V (AC-23A)
Rated Conditional Short Circuit Current	10 KA at 400 V - associated fuse 200 A aM 10 kA at 400 V - associated fuse 200 A gG
[Icm] Rated Short Circuit Making Capacity	2.8 kA at 400 V at Ipeak
Intermittent duty class	30
Suitability for isolation	Yes
[Uimp] rated impulse withstand voltage	8 kV
[Icw] rated short-time withstand Rms current	2100 A at 400 V duration: 1 s
Mechanical Durability	30000 cycles
Electrical Durability	30000 Cycles AC-21 30000 cycles DC-1...5
IEC Terminal Connection	Power circuit: screw clamp terminals70 mm ² - flexible - with cable end Power circuit: screw clamp terminals95 mm ² - solid
Tightening Torque	Power circuit: 22.6 N.m - on screw clamp terminals

Height	125 mm
Width	90 mm
Depth	90 mm
Product Weight	0.9 kg

Environment

Standards	IEC 60947-3
Product Certifications	GL CSA UL
Degree of Protection	IP20 conforming to IEC 60529
Protective Treatment	TC
Mechanical Robustness	Vibrations 10...150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27
Ambient Air Temperature for Operation	-20...50 °C
Fire Resistance	960 °C conforming to IEC 60695-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.068 kg
Package 1 Height	10 cm
Package 1 width	11.5 cm
Package 1 Length	13.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------