



Main

Range	ComPact
Product name	Compact INS
Product or component type	Switch disconnector
Poles description	4P
Network type	DC AC
Network frequency	50/60 Hz
[Ie] rated operational current	AC-22A: 40 A AC 50/60 Hz 220/240 V AC-22A: 40 A AC 50/60 Hz 380/415 V AC-22A: 40 A AC 50/60 Hz 440/480 V AC-22A: 40 A AC 50/60 Hz 500 V AC-23A: 32 A AC 50/60 Hz 500 V AC-23A: 40 A AC 50/60 Hz 220/240 V AC-23A: 40 A AC 50/60 Hz 380/415 V AC-23A: 40 A AC 50/60 Hz 440/480 V DC-22A: 40 A DC 125 V 2 poles in series DC-23A: 40 A DC 125 V 2 poles in series DC-22A: 40 A DC 250 V 4 poles in series DC-23A: 40 A DC 250 V 4 poles in series
[Ui] rated insulation voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	40 A at 60 °C
[Icm] rated short-circuit making capacity	15 kA switch-disconnector alone 500 V AC at 50/60 Hz 75 kA with upstream protection circuit breaker 500 V AC at 50/60 Hz
[Ue] rated operational voltage	500 V AC 50/60 Hz 250 V DC
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No
Pollution degree	3

Complementary

Control type	Rotary handle
Handle colour	Red
Mounting mode	Fixed
Mounting support	Plate DIN rail
Upside connection	Front
Downside connection	Front
Cable cross section	1.5...50 mm ²
Maximum power	AC-23: 11 kW at 220/240 V AC 50/60 Hz AC-23: 18.5 kW at 500/525 V AC 50/60 Hz AC-23: 20 kW at 380/415 V AC 50/60 Hz AC-23: 22 kW at 440 V AC 50/60 Hz
Rated duty	Uninterrupted
Intermittent duty class	Class 120 - 60 %
Enclosure dimensions for Ithe	190 mm x 115 mm x 55 mm

[I _{cw}] rated short-time withstand current	0.067 kA during 20 s conforming to IEC 60947-3 1.73 kA during 3 s conforming to IEC 60947-3 3 kA during 1 s conforming to IEC 60947-3 5.5 kA during 30 s conforming to IEC 60947-3
Mechanical durability	20000 cycles
Electrical durability	AC-22A: 1500 cycles 220/240 V AC 50/60 Hz AC-22A: 1500 cycles 380/415 V AC 50/60 Hz AC-22A: 1500 cycles 440 V AC 50/60 Hz AC-22A: 1500 cycles 500 V AC 50/60 Hz AC-23A: 1500 cycles 220/240 V AC 50/60 Hz AC-23A: 1500 cycles 380/415 V AC 50/60 Hz AC-23A: 1500 cycles 440 V AC 50/60 Hz AC-23A: 1500 cycles 500 V AC 50/60 Hz DC-22A: 1500 cycles 250 V DC 4 poles in series DC-23A: 1500 cycles 250 V DC 4 poles in series
Connection pitch	18 mm
Height	85 mm
Width	90 mm
Depth	62.5 mm
Net weight	0.6 kg

Environment

Standards	IEC 60947-3 IEC 60947-1
Product certifications	KEMA-KEUR CCC
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	655 g
Package 1 Height	9.5 cm
Package 1 width	10 cm
Package 1 Length	10 cm
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Weight	12.277 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------