Product data sheet Characteristics

33444

molded case switch-disconnector Compact NS1000 NA - 1000 A - 3 poles



Main ComPact NS Product name Device short name Compact NS1000 NA Product or component Switch disconnector type Device application Distribution Offer type C4 Poles description 3P AC Network type Performance level NΑ Suitability for isolation Yes conforming to IEC 60947-3

Complementary

Network frequency	50/60 Hz		
Control type	Motor mechanism		
Mounting mode	Fixed		
Mounting support	Chassis		
[le] rated operational current	AC-23A: 1000 A AC 50/60 Hz 220/240 V AC-23A: 1000 A AC 50/60 Hz 380/415 V AC-23A: 1000 A AC 50/60 Hz 440/480 V AC-23A: 1000 A AC 50/60 Hz 500/525 V AC-23A: 1000 A AC 50/60 Hz 660/690 V		
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-3		
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-3		
[Ith] conventional free air thermal current	1000 A at 60 °C		
[lcw] rated short-time withstand current	25 KA during 0.5 s conforming to IEC 60947-3 4 kA during 20 s conforming to IEC 60947-3		
[Icm] rated short-circuit making capacity	52 kA 690 V AC at 50/60 Hz		
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3		
Contact position indicator	Yes		
Visible break	No		
Mechanical durability	6000 cycles conforming to IEC 60947-3		
Electrical durability	1000 cycles 440 V AC 50/60 Hz conforming to IEC 60947-3		
Connection pitch	70 mm		
Height	327 mm		
Width	210 mm		
Depth	147 mm		
Net weight	14 kg		

Environment

Standards	IEC 60947-3	
Product certifications	ASTA ASEFA	
Pollution degree	3 conforming to IEC 60947-3	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-5085 °C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	11.938 kg	
Package 1 Height	36 cm	
Package 1 width	23 cm	
Package 1 Length	39 cm	

Offer Sustainability

REACh Regulation	REACh Declaration		
EU RoHS Directive	Compliant EEU RoHS Declaration		
Mercury free	Yes		
RoHS exemption information	₫Yes		
China RoHS Regulation	[☑] China RoHS Declaration		
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins		
PVC free	Yes		

Contractual warranty

<u></u>		
Warranty	18 months	