33450

Network type

Performance level

Suitability for isolation

basic switch disconnector, Compact NS630b NA, withdrawable, electrically operated, 630 A, 690 VAC 50/60 Hz, 3 poles



Main Product name ComPact NS Device short name Compact NS630b NA Product or component type Switch disconnector Device application Distribution Offer type C4 Poles description 3P

Yes conforming to IEC 60947-3

AC

NΑ

Complementary

Complementary	
Network frequency	50/60 Hz
Control type	Motor mechanism with external connector
	Motor mechanism
Mounting mode	Drawout
Mounting support	Chassis
[le] rated operational current	AC-23A: 630 A AC 50/60 Hz 220/240 V
	AC-23A: 630 A AC 50/60 Hz 380/415 V
	AC-23A: 630 A AC 50/60 Hz 440/480 V
	AC-23A: 630 A AC 50/60 Hz 500/525 V
	AC-23A: 630 A AC 50/60 Hz 660/690 V
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-3
[Ith] conventional free air thermal current	630 A at 60 °C
[lcw] rated short-time withstand current	25 KA during 0.5 s conforming to IEC 60947-3
	4 kA during 20 s conforming to IEC 60947-3
[lcm] rated short-circuit making capacity	52 kA 690 V AC at 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Mechanical durability	6000 cycles conforming to IEC 60947-3
Electrical durability	1000 cycles 440 V AC 50/60 Hz conforming to IEC 60947-3
Connection pitch	70 mm
Height	327 mm
Width	210 mm
Depth	147 mm
Net weight	14 kg

Environment

Standards	IEC 60947-3	
Product certifications	ASTA ASEFA	
Pollution degree	3 conforming to IEC 60947-3	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-5085 °C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	14.711 kg	
Package 1 Height	36 cm	
Package 1 width	23 cm	
Package 1 Length	39 cm	

Offer Sustainability

REACh Declaration
Compliant EEU RoHS Declaration
Yes
€Yes
☑ China RoHS Declaration
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Marranty	19 months
vvairanty	18 months