



Main

Range	ComPact
Product name	INSJ400
Switch-disconnector name	Interpact INSJ400
Poles description	3P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	250 A AC 50/60 Hz 600 V
[Uimp] rated impulse withstand voltage	8 kV
[Icm] rated short-circuit making capacity	100 KA protected by circuit breaker NSJ400 - 400A 480 V AC at 50/60 Hz 150 KA protected by circuit breaker NSJ400 - 400A 240 V AC at 50/60 Hz 20 KA protected by any protection device 600 V AC at 50/60 Hz 25 KA protected by circuit breaker NSJ400 - 400A 600 V AC at 50/60 Hz 50 kA with class T or RK fuses 400 A 600 V AC at 50/60 Hz
[Ue] rated operational voltage	600 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes

Complementary

Control type	Rotary handle
Mounting mode	Fixed
Mounting support	Plate
Upside connection	Front
Downside connection	Rear Front
Mechanical durability	5000 cycles conforming to UL 489
Electrical durability	1000 cycles full load
Height	205 mm
Width	185 mm
Depth	130 mm
Net weight	4.6 kg

Environment

Standards	UL 489 CSA C22.2 No 5.2
-----------	----------------------------

Packing Units

Package 1 Weight	5.068 kg
Package 1 Height	18.500 cm
Package 1 width	18.000 cm
Package 1 Length	20.700 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------