



Main

Range	Masterpact
Product name	Masterpact NW
Product or component type	Switch disconnector
Device short name	Masterpact NW08
Switch-disconnector name	Masterpact NW08NA
Device application	Protection
Poles description	4P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	800 A AC 50/60 Hz 690 V
[Ui] rated insulation voltage	1000 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	12 kV conforming to IEC 60947-3
[Icm] rated short-circuit making capacity	88 kA 220...690 V AC at 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3
Breaking capacity code	NA
Suitability for isolation	Yes conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Pollution degree	4 conforming to IEC 60664-1

Complementary

Control type	Push-button
Mounting mode	Fixed
Operating rate	10 cyc/h maximum
[Icw] rated short-time withstand current	42 kA during 1 s conforming to IEC 60947-3
Mechanical durability	12500 Cycles without maintenance conforming to IEC 60947-3 25000 cycles with maintenance conforming to IEC 60947-3
Electrical durability	AC-23A: 10000 cycles 440 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 AC-23A: 10000 cycles 690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3 AC-3: 6000 cycles 440/690 V AC 50/60 Hz without maintenance conforming to IEC 60947-3
Connection pitch	115 mm
Height	352 mm
Width	537 mm
Depth	297 mm
Net weight	80 kg

Environment

Standards	IEC 60947-3
Product certifications	ASEFA ASTA
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-35...85 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------