



### Main

|                           |                         |
|---------------------------|-------------------------|
| Range of product          | PowerPact multistandard |
| Range                     | PowerPact               |
| Product name              | H-Frame                 |
| Device short name         | H-Frame                 |
| Product or component type | Circuit breaker         |
| Device application        | Distribution            |

### Complementary

|                                        |                                                                                                                                                                                                                                                                                                                                                                    |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Poles description                      | 3P                                                                                                                                                                                                                                                                                                                                                                 |
| Control type                           | Toggle                                                                                                                                                                                                                                                                                                                                                             |
| Mounting mode                          | Fixed                                                                                                                                                                                                                                                                                                                                                              |
| Mounting support                       | Flush<br>Backplate<br>DIN rail                                                                                                                                                                                                                                                                                                                                     |
| [In] rated current                     | 150 A at 40 °C                                                                                                                                                                                                                                                                                                                                                     |
| [Ui] rated insulation voltage          | 750 V AC 50/60 Hz conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                        |
| [Uimp] rated impulse withstand voltage | 8 kV IEC 60947-2                                                                                                                                                                                                                                                                                                                                                   |
| [Ue] rated operational voltage         | 525 V AC 50/60 Hz conforming to IEC 60947-2                                                                                                                                                                                                                                                                                                                        |
| Breaking capacity code                 | HL                                                                                                                                                                                                                                                                                                                                                                 |
| Suitability for isolation              | Yes                                                                                                                                                                                                                                                                                                                                                                |
| Utilisation category                   | Category A                                                                                                                                                                                                                                                                                                                                                         |
| Mechanical durability                  | 5000 cycles                                                                                                                                                                                                                                                                                                                                                        |
| Electrical durability                  | 1000 cycles                                                                                                                                                                                                                                                                                                                                                        |
| Connection pitch                       | 45 mm                                                                                                                                                                                                                                                                                                                                                              |
| Local signalling                       | ON/OFF indication                                                                                                                                                                                                                                                                                                                                                  |
| Contact position indicator             | Yes                                                                                                                                                                                                                                                                                                                                                                |
| Trip unit rating                       | 2250 A                                                                                                                                                                                                                                                                                                                                                             |
| Breaking capacity                      | Icu: 100 kA at 220/240 V - AC conforming to IEC 947-2<br>Icu: 65 kA at 380/415 V - AC conforming to IEC 947-2<br>Icu: 65 kA at 440/480 V - AC conforming to IEC 947-2<br>Icu: 25 kA at 500/525 V - AC conforming to IEC 947-2<br>100 KA at 240 V - AC conforming to UL 489<br>65 KA at 480 V - AC conforming to UL 489<br>25 kA at 600 V - AC conforming to UL 489 |
| [Ics] rated service breaking capacity  | Ics: 125 kA at 220/240 V - AC conforming to IEC 947-2<br>Ics: 100 kA at 380/415 V - AC conforming to IEC 947-2<br>Ics: 100 kA at 440/480 V - AC conforming to IEC 947-2<br>Ics: 50 kA at 500/525 V - AC conforming to IEC 947-2                                                                                                                                    |
| Overvoltage category                   | II                                                                                                                                                                                                                                                                                                                                                                 |
| Provision for padlocking               | Non padlockable                                                                                                                                                                                                                                                                                                                                                    |
| Height                                 | 163 mm                                                                                                                                                                                                                                                                                                                                                             |
| Width                                  | 104 mm                                                                                                                                                                                                                                                                                                                                                             |
| Depth                                  | 86 mm                                                                                                                                                                                                                                                                                                                                                              |

|                        |                                                                                  |
|------------------------|----------------------------------------------------------------------------------|
| Standards              | UL 489<br>IEC 60947-2<br>CSA C22.2 No 5<br>NEMA AB1<br>W-C-375B/GEN<br>NMX J-266 |
| Product certifications | CCC<br>CE                                                                        |
| Net weight             | 2.2 kg                                                                           |

## Environment

|                                       |                                                            |
|---------------------------------------|------------------------------------------------------------|
| IP degree of protection               | IP40 conforming to IEC 60529                               |
| IK degree of protection               | IK07 conforming to IEC 62262                               |
| Pollution degree                      | 3 conforming to IEC 60947-1<br>3 conforming to IEC 60664-1 |
| Ambient air temperature for operation | 40 °C                                                      |
| Ambient air temperature for storage   | -50...85 °C                                                |

## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 2.357 kg |
| Package 1 Height | 1.450 dm |
| Package 1 width  | 1.900 dm |
| Package 1 Length | 2.150 dm |

## Offer Sustainability

|                            |                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                             |
| REACH Regulation           |  <a href="#">REACH Declaration</a>              |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                               |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile        |  <a href="#">End Of Life Information</a>       |
| PVC free                   | Yes                                                                                                                               |