

Product data sheet

Characteristics

33890

mechanical interlocking kit, ComPact NS630b to NS1600, for 2 devices with extended rotary handles



Main

Product or component type	Mechanical interlock
Accessory / separate part category	Interlocking accessory
Range compatibility	ComPact NS630b...1600

Complementary

Source-changeover interlock	Interlocking 2 sources
Interlocked device	Compact NS630b...1600
Control type	Extended rotary handle
Accessory / separate part category	Spare part for Compact NS630b...1600

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	807 g
Package 1 Height	2.7 cm
Package 1 width	18 cm
Package 1 Length	43 cm
Unit Type of Package 2	S04
Number of Units in Package 2	18
Package 2 Weight	15.526 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
PVC free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months
----------	-----------
