



### Main

Range of product	Acti 9
Product name	Acti 9 iSO
Product or component type	Bell
Device short name	ISO

### Complementary

[Us] rated supply voltage	230 V AC at 50/60 Hz
Power consumption in VA	5 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	72 mm
Net weight	77 g
Auxiliary connection terminal	Tunnel type terminalsrigid 4 mm <sup>2</sup> Tunnel type terminalsflexible 4 mm <sup>2</sup> Tunnel type terminalsflexible with ferrule 4 mm <sup>2</sup>
Wire stripping length	12 mm for bottom connection
Tightening torque	1.3 N.m bottom

### Environment


Noise level	80 dB
Type of sound	Bell
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Ambient air temperature for operation	-10...40 °C
Ambient air temperature for storage	-25...60 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	60 g
Package 1 Height	6.6 cm
Package 1 width	1.8 cm
Package 1 Length	8.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	768 g
Package 2 Height	8 cm
Package 2 width	10 cm

Package 2 Length	22.7 cm
Unit Type of Package 3	S03
Number of Units in Package 3	144
Package 3 Weight	9.746 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#"> EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#"> Yes</a>
China RoHS Regulation	<a href="#"> China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product