

# Product data sheet

## Characteristics

# A9E15122

2 ways low level switch iCME 10 A 0,1..5 CA  
0,05..3 CCA 2P U 1..440 VAC/VCCV CA



### Main

Range of product	Acti 9
Product name	Acti 9 iCM
Product or component type	Selector switch
Device short name	ICME
Device application	Electrical circuit control
Contacts type and composition	1 NO + 1 NC
Standards	EN 60947-3 IEC 60947-3 VDE 0660 part 107 UL

### Complementary

Maximum operating voltage	440 V
Control type	Rotary handle 2 positions
Marking	1 - 2
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Height	60 mm
Width	36 mm
Depth	75 mm
Net weight	44 g
Colour	White
Mechanical durability	1000000 cycles
Electrical durability	AC-21A: 200000 cycles
Connections - terminals	Jumper terminals 1.5 mm <sup>2</sup>
Wire stripping length	9 mm for downside connection
Tightening torque	1 N.m downside

### Environment

IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20...55 °C
Ambient air temperature for storage	-25...80 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	67 g
Package 1 Height	4.3 cm
Package 1 width	7.6 cm
Package 1 Length	8.4 cm
Unit Type of Package 2	S03
Number of Units in Package 2	80
Package 2 Weight	5.847 kg
Package 2 Height	30 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------