


### Main

|                           |                 |
|---------------------------|-----------------|
| Range                     | Masterpact      |
| Device short name         | MCH             |
| Product or component type | Motor mechanism |
| Device application        | Control         |
| Range compatibility       | Masterpact MTZ1 |

### Complementary

|                                 |                                    |
|---------------------------------|------------------------------------|
| Control type                    | Standard                           |
| Mounting mode                   | Drawout                            |
| [Uc] control circuit voltage    | 277...415 V AC 50/60 Hz            |
| Threshold tripping voltage      | 0.85...1.1 Un                      |
| Maximum power consumption in VA | 180 VA                             |
| Overcurrent protection          | 2...3 x In 0.1 s                   |
| Maximum charging time           | 3 s                                |
| Maximum operating frequency     | <= 3 cycles per minute             |
| Provided contact                | Limit switch contact at 240 V 10 A |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile        |  <a href="#">End Of Life Information</a>       |