



## Main

Range	Masterpact
Product or component type	Motor mechanism
Device application	Control
Range compatibility	Masterpact MTZ2 Masterpact MTZ3

## Complementary

Control type	Standard
[Uc] control circuit voltage	440...480 V AC 50/60 Hz
Threshold tripping voltage	0.85...1.1 Un
Maximum power consumption in VA	180 VA
Overcurrent protection	2...3 x In 0.1 s
Maximum charging time	4 s
Maximum operating frequency	<= 3 cycles per minute
Provided contact	Limit switch contact at 240 V 10 A

## Environment

Provided equipment	1 instruction sheet
Offer type	Spare part

## Packing Units

Package 1 Weight	1.986 kg
Package 1 Height	23.000 cm
Package 1 width	14.000 cm
Package 1 Length	14.000 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>