



**Main**

Range of product	Acti 9
Device short name	iATLs
Product or component type	Remote indication auxiliary
Signal contacts composition	1 C/O
Signalling circuit voltage	24 V AC/DC: 10 mA 12...240 V AC: 50/60 Hz 6 A 12...24 V DC: 6 A 15...240 V AC: 50/60 Hz 2 A 13...24 V DC: 2 A
[Uc] control circuit voltage	24...240 V AC 50/60 Hz 24...240 V DC

**Complementary**

[Ui] rated insulation voltage	440 V
[Uiimp] rated impulse withstand voltage	4 kV
Mounting mode	Fixed, on right side of TL
Mounting support	DIN rail
9 mm pitches	1
Height	81 mm
Width	9 mm
Depth	69 mm
Colour	White
Connections - terminals	Tunnel type terminals 0.5...4 mm² - rigid Tunnel type terminals 0.5...4 mm² - rigid - with cable end Tunnel type terminals 1...4 mm² - flexible Tunnel type terminals 1...4 mm² - flexible - with cable end
Wire stripping length	11 mm
Tightening torque	1 N.m
Range compatibility	Acti 9 iTL iTL Acti 9 iTL iTLi Acti 9 iTL iTLs Acti 9 iTL iTLc Acti 9 iTL iTLm
Product compatibility	ITL (32 A) ITL (16 A)

**Environment**

Overvoltage category	III
IP degree of protection	IP20 conforming to IEC 60529
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...70 °C
Standards	EN/IEC 60669-2-2

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	40 g
Package 1 Height	2 cm
Package 1 width	8 cm
Package 1 Length	9.4 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	530 g
Package 2 Height	9 cm
Package 2 width	10 cm
Package 2 Length	27 cm
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Weight	5.277 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------