



### Main

Range of product	Acti 9
Device short name	iATLc+c
Product or component type	Multilevel centralized control auxiliary
[Uc] control circuit voltage	24...240 V AC 50/60 Hz impulse

### Complementary

[Ui] rated insulation voltage	440 V
[Uiimp] rated impulse withstand voltage	4 kV
Remote control type	2 entries for switch
Mounting mode	Fixed
Mounting support	DIN rail
9 mm pitches	2
Height	86 mm
Width	18 mm
Depth	71 mm
Colour	White
Connections - terminals	Tunnel type terminals 0.5...4 mm <sup>2</sup> - rigid Tunnel type terminals 0.5...4 mm <sup>2</sup> - rigid - with cable end Tunnel type terminals 1...4 mm <sup>2</sup> - flexible Tunnel type terminals 1...4 mm <sup>2</sup> - flexible - with cable end
Wire stripping length	11 mm
Tightening torque	1 N.m
Range compatibility	Acti 9 iTL iTLc Acti 9 iTL iATLc Acti 9 iTL iATLc+s

### Environment

Overvoltage category	III
IP degree of protection	IP20 conforming to IEC 60529
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...70 °C
Standards	EN/IEC 60669-2-2

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	75 g
Package 1 Height	2.9 cm
Package 1 width	8 cm
Package 1 Length	9.5 cm

Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	640 g
Package 2 Height	10 cm
Package 2 width	9 cm
Package 2 Length	27 cm
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Weight	6.288 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

### Contractual warranty

Warranty	18 months
----------	-----------