



Main

Range	PowerLogic
Product name	PowerLogic BCPMSC
Product or component type	Multi-circuit energy meter
Device short name	BCPMSC
Model type	Advanced + ethernet
Power monitoring	Basic instrumentation
Energy management	Sub billing and cost allocation
Device application	Sub billing
Power quality analysis	Voltage sag and swell detection
Type of measurement	Voltage Current Frequency Active power Power factor Active energy
[Us] rated supply voltage	90...277 V AC 50/60 Hz +/- 1 %
Network frequency	50 Hz 60 Hz

Complementary

Current transformer input	Current 1 V Current 0.333 V84 x
Update time	1.8 s
Measurement voltage	90...277 V phase to neutral 150...480 V phase to phase
Measurement accuracy	Branch current 2 % 0.25...2 A Branch current 2 % 2...100 A Mains current 2 % 1...100 % Mains current 2 % 2...100 % Voltage 2 % 90...277 V
Sampling rate	256 samples/cycle
Provided equipment	4 x adapter board 0 x current transformer
Communication port protocol	Modbus RTU BACnet IP BACnet MS/TP Modbus TCP SNMP v2
Communication port support	RS485 Ethernet
Communication of data	Under voltage alarm High current alarm High-high current alarm Low-low current alarm Over voltage alarm Low current alarm

Environment

Mounting mode	Clip-on
Mounting support	Board
Relative humidity	95 %
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...70 °C
Operating altitude	3000 m
Standards	ANSI C12.1 EN 61010 IEC 61010-1
Product certifications	UL 508
Width	288 mm
Height	146 mm
Net weight	1.5 kg

Packing Units

Package 1 Weight	4772.730 g
Package 1 Height	152.000 mm
Package 1 width	305.000 mm
Package 1 Length	508.000 mm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins