Product data sheet Characteristics

A9MEM3310

iEM3310 energy meter - 125 A - 1 pulse O - MID





Main

Range	Acti 9
Range of product	Acti 9 iEM3000
Device short name	IEM3310
Product or component type	Energy meter

Complementary

Poles description	3P 1P + N
	3P + N
Type of measurement	Active energy
Device application	Sub billing Partial meter
Accuracy class	Class 1 active energy conforming to IEC 62053-21 Class 1 active energy conforming to IEC 61557-12 Class B active energy conforming to EN 50470-3
Input type	Direct input
[In] rated current	125 A
Rated voltage	100277 V 173480 V
Network frequency	60 Hz 50 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Measurement current	0125 A
Maximum value measured	99999999.9 kWh
Communication port protocol	-
Communication port support	-
Local signalling	Green indicator light: power ON Yellow flashing LED: accuracy checking
Number of inputs	0
Number of outputs	1 pulse
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Screw terminals 50 mm² cable(s)
Overvoltage category	III

Standards	IEC 62053-23	
	IEC 61010	
	UL 61010-1	
	IEC 61557-12	
	IEC 61036	
	IEC 62053-21	
Product certifications	CE conforming to IEC 61010 (safety)	
	CE conforming to EN 61557-12 (power monitor)	
	CE conforming to IEC 61326-1 (EMC)	
	CULus conforming to UL 61010 (safety)	
	CULus conforming to ANSI C12.20 (sub-meter)	
	EAC (sub-meter)	
	RCM conforming to NMI M 6-1 (sub-meter)	
	UL	
	MID conforming to EN 50470-3 (sub-meter)	
	MID conforming to EN 62052 (sub-meter)	

Environment

IP degree of protection	IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529
Pollution degree	2
Relative humidity	595 % at 50 °C
Ambient air temperature for operation	-2555 °C - MID -2560 °C - NMI -2560 °C - IEC
Ambient air temperature for storage	-4085 °C
Operating altitude	< 2000 m
Colour	White
9 mm pitches	14
Width	126 mm
Height	103.2 mm
Depth	69.3 mm

Packing Units

Package 1 Weight	0.685 kg	
Package 1 Height	8.500 cm	
Package 1 width	11.500 cm	
Package 1 Length	13.200 cm	

Offer Sustainability

 		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	