

Product data sheet

Characteristics

A9MEM3465

iEM3465 energy meter - BACnet - 1 DI - 1 DO - multi-tariff - LVCT



Main

Range	Acti 9
Range of product	Acti 9 iEM3000
Device short name	IEM3465
Product or component type	Energy meter

Complementary

Poles description	3P 1P + N 3P + N
Type of measurement	Active and reactive energy Active and reactive power Current Voltage
Metering type	Active, reactive, apparent energy (signed, four quadrant)
Device application	Sub billing Multi-tariff Partial meter
Accuracy class	Class 0.5S active energy conforming to IEC 62053-22 Class 0.5S active energy conforming to ANSI C12.20
Input type	Split core current transducer 0.333 V or 1 V
Rated voltage	100...277 V +/- 20 % 173...480 V +/- 20 %
Network frequency	60 Hz 50 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Measurement current	1...32767000 mA
Maximum value measured	99999999.9 kWh 99999999 MWh
Tariff input	Tariff (4)
Communication port protocol	BACnet at 9.6, 19.2, 38.4, 57.6, 76.8 kbauds
Communication port support	Screw terminal block: RS485
Local signalling	Green indicator light: power ON Yellow flashing LED: accuracy checking Alarm: overload
Number of inputs	1 digital 0...5 V/11...40 V 24 V DC
Number of outputs	1 digital (static)
Output voltage	5...40 V DC@50 mA
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Current circuit: screw terminals 6 mm ² cable(s) Voltage circuit: screw terminals 2.5 mm ² cable(s) Input/Output circuit: screw terminals 1.5 mm ² cable(s) Communication: screw terminals 2.5 mm ² cable(s)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Tightening torque	Input/Output circuit: 0.5 N.m Philips screwdriver Voltage circuit: 0.5 N.m Philips screwdriver Current circuit: 0.8 N.m pozidriv screwdriver Communication: 0.5 N.m Philips screwdriver
Wire stripping length	Input/Output circuit: 6 mm Voltage circuit: 8 mm Current circuit: 8 mm Communication: 7 mm
Standards	UL 61010-1 IEC 62053-21 IEC 61036 IEC 61010 IEC 61557-12 IEC 62053-23
Product certifications	CE conforming to IEC 61010 (safety) CE conforming to EN 61557-12 (power monitor) CE conforming to IEC 61326-1 (EMC) CULus conforming to UL 61010 (safety) CULus conforming to ANSI C12.20 (sub-meter) EAC (sub-meter) RCM conforming to NMI M 6-1 (sub-meter) UL

Environment

IP degree of protection	IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529
IK degree of protection	IK08
Pollution degree	2
Relative humidity	5...95 % at 36 °C
Ambient air temperature for operation	-25...70 °C - IEC
Ambient air temperature for storage	-40...85 °C
Operating altitude	< 3000 m
Colour	White
9 mm pitches	10
Width	90 mm
Height	87 mm
Depth	69 mm

Packing Units

Package 1 Weight	0.359 kg
Package 1 Height	8.800 cm
Package 1 width	9.800 cm
Package 1 Length	10.500 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	<input checked="" type="checkbox"/> End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins