



### Main

Range	PowerLogic
Product or component type	Remote display
Device application	Human-machine dialogue application
Range compatibility	PowerLogic PM5000
Display type	Backlit LCD

### Complementary

Display colour	Monochrome
Display resolution	128 x 128 pixels
Display size	67 x 62.5 mm
Information displayed	Power Energy consumption Harmonic distortion Frequency Voltage Current
Messages display capacity	6 lines Graphic objects (bargraph, button, light...)
Local signalling	Communication: LED (green) Programming indication: LED (amber)
Control type	4 x push-button
Connector type	RJ45
Mounting mode	Flush-mounted
Mounting support	Framework remote display
Width	96 mm
Height	96 mm
Embedding depth	21 mm
Projecting depth	27 mm

### Environment

IP degree of protection	IP52 conforming to IEC 60529
Relative humidity	5...95 % at 37 °C
Operating altitude	0...3000 m
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

### Packing Units

Package 1 Weight	320.000 g
Package 1 Height	70.000 mm
Package 1 width	100.000 mm
Package 1 Length	100.000 mm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins