



**Main**

Range	TeSys
Device short name	LUL
Product or component type	Communication module
Product compatibility	LUCL LUCC LUCB LUCM LUCA LUCD
Device application	Communication
Range compatibility	TeSys U LUB non reversing power base TeSys U LU2B reversing power base

**Complementary**

Main function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	RS485 multidrop
Bus type	Modbus
Cable connector type	RJ45 front panel
Communication port protocol	Modbus RTU
Addressing	0...31
Transmission rate	19200 bit/s
Return time	30 ms
Number of inputs	2
Logic input	Positive at 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 0 10 ms +/- 30 % change to state 1
Input type	Resistive
Number of outputs	2 dedicated to starter-controller coil operation 1
[Us] rated supply voltage	24 V DC
Output current	<= 500 mA
Protection type	GG fuse 1 A
Switching current capacity	0.5 mA at 24 V
Local signalling	3 LEDs front panel
Connection pitch	3.81 mm
Connections - terminals	Screw clamp terminals 1 cable(s) 0.14...1 mm <sup>2</sup> flexible without cable end Screw clamp terminals 1 cable(s) 0.14...1 mm <sup>2</sup> rigid without cable end Screw clamp terminals 1 cable(s) 0.25...0.5 mm <sup>2</sup> flexible with cable end Screw clamp terminals 1 cable(s) 0.25...1 mm <sup>2</sup> flexible with cable end Screw clamp terminals 2 cable(s) 0.14...0.5 mm <sup>2</sup> rigid without cable end Screw clamp terminals 2 cable(s) 0.14...0.75 mm <sup>2</sup> flexible without cable end Screw clamp terminals 2 cable(s) 0.25...0.34 mm <sup>2</sup> flexible with cable end Screw clamp terminals 2 cable(s) 0.5 mm <sup>2</sup> flexible with cable end
Associated cable type	AWG 26...AWG 16
Tightening torque	0.2...0.25 N.m2.5 mm
Net weight	0.08 kg

## Environment

Ambient air temperature for operation	-25...55 °C
IP degree of protection	IP20 conforming to IEC 60529

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	84 g
Package 1 Height	5.3 cm
Package 1 width	4.9 cm
Package 1 Length	11.4 cm

## Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------