

LUALB1

Current limiter disconnecter, TeSys U,
32A/690V, activation 50kA, Iq 130kA@440V,
mounting on power base



Main

Range	TeSys
Range of product	TeSys U
Device short name	LUA
Product or component type	Limiter disconnecter
Product compatibility	LUB LU2B

Complementary

[Ith] conventional free air thermal current	32 A
Breaking capacity	70 KA at 690 V 130 kA at 440 V
[Ui] rated insulation voltage	690 V conforming to EN 60947-1 690 V conforming to IEC 60947-1
Mounting mode	Direct
Connections - terminals	Connector 1 x 1...10 mm ² flexible without cable end Connector 1 x 1...6 mm ² flexible with cable end Connector 2 x 1...6 mm ² flexible with cable end Connector 2 x 1...6 mm ² flexible without cable end Connector 1 x 1.5...10 mm ² solid Connector 2 x 1.5...6 mm ² solid
Tightening torque	1.9...2.5 N.M flat Ø 6 mm 1.9...2.5 N.m Philips No 2
Net weight	0.31 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	327 g
Package 1 Height	5.2 cm
Package 1 width	11 cm
Package 1 Length	13.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins