



### Main

Product or component type	Cartridge
Device short name	C40-350
Surge arrester type	Electrical distribution network

### Complementary

Surge arrester class type	Type 2
Surge arrester technology	MOV
Earthing system	TN TT
[Ue] rated operational voltage	230 V AC 50 Hz
Nominal discharge current	20 kA
Maximum discharge current	40 kA
[Uc] maximum continuous operating voltage	350 V
Maximum [Up] voltage protection level	<1.4 kV type 2
Local signalling	White/red flag
Mounting mode	Plug-in
Mounting support	Into SPD module
9 mm pitches	1.3
Height	50 mm
Width	12 mm
Depth	57 mm
Colour	White (RAL 9003)
Material	PBT (polybutylene terephthalate)
Response time	< 25 ns



### Environment

Standards	IEC 61643-1 EN 61643-11
Product certifications	KEMA-KEUR NF
IP degree of protection	IP20 front face:
Relative humidity	5...90 %
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	59 g
Package 1 Height	2.1 cm
Package 1 width	6.8 cm
Package 1 Length	9.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	786 g
Package 2 Height	11 cm
Package 2 width	8 cm
Package 2 Length	27 cm
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Weight	7.787 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts & cables product

## Contractual warranty

Warranty	18 months
----------	-----------