



Main

Range of product	Acti 9
Product name	Acti 9 PRD1 Master
Product or component type	Surge arrester with pluggable cartridge
Device short name	PRD1 Master
Device application	Distribution
Poles description	3P + N
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network
Earthing system	TT TN-S

Complementary

Surge arrester class type	Type 1
Surge arrester technology	Spark gap
[Ue] rated operational voltage	230/400 V AC (+/- 10 %) at 50/60 Hz
[In] nominal discharge current	Common mode: 100 kA (N/PE) Differential mode: 25 kA (L/N)
[Iimp] impulse current	Common mode: 100 kA N/PE 50 A.s Differential mode: 25 kA L/N 12.5 A.s
[Uc] maximum continuous operating voltage	Differential mode: 350 V L/N Common mode: 350 V N/PE
Maximum [Up] voltage protection level	Common mode <1.5 kV type 2 N/PE Differential mode <1.5 kV type 2 L/N
[If] follow current	0.1 kA common mode N/PE 50 kA differential mode L/N
Disconnecter device type	Associated fuse gG 315 A standard Associated circuit breaker Compact NSX100F 100 A curve C - Icu 36 kA Associated circuit breaker Compact NSX100N 100 A curve C - Icu 50 kA
Signalling circuit voltage	1 A/250 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	16
Height	90 mm
Width	142.8 mm
Depth	70 mm
Net weight	1.31 kg
Colour	Anthracite grey (RAL 7016)
Material	PBT (polybutylene terephthalate)
Response time	< 100 ns
Connections - terminals	Tunnel type terminal (downside) 2.5...35 mm ² Tunnel type terminal (upside) 2.5...35 mm ²
Tightening torque	4.5 N.m

Environment

Standards	EN 61643-11:2012 IEC 61643-11:2011
Product certifications	CE
Quality labels	KEMA-KEUR
IP degree of protection	IP40 on front face: conforming to IEC 60529 IP20 built-in: conforming to IEC 60529
IK degree of protection	IK05 conforming to IEC 62262
Relative humidity	5...90 %
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.574 kg
Package 1 Height	9.5 cm
Package 1 width	14 cm
Package 1 Length	17.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Weight	11.406 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------