



Main

Range	Masterpact
Device short name	MX diag & com
Product or component type	Voltage release
Device application	Control
Range compatibility	Masterpact MTZ2 circuit-breaker Masterpact MTZ3 circuit-breaker Masterpact MTZ1 circuit-breaker
Voltage release type	Opening coil

Complementary

Control type	Communicating
Signalling function	Electrical push-button activated Ready to close or open Coil powered Error
[Un] voltage power supply	24...30 V DC 24 V AC 50/60 Hz
Threshold tripping voltage	0.7...1.1 Un on opening
Holding power consumption	4.5 W
Circuit breaker mounting mode	Fixed
Maximum response time	60 ms on opening for Masterpact MTZ1 60 ms on opening for Masterpact MTZ2 60 ms on opening for Masterpact MTZ3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.162 kg
Package 1 Height	9 cm
Package 1 width	6 cm
Package 1 Length	4 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information