



Main

| | |
|---------------------------|-------------------------------------------------------------------------------------------------------|
| Range | Masterpact |
| Device short name | XF |
| Product or component type | Voltage release |
| Device application | Control |
| Range compatibility | Masterpact MTZ2 circuit-breaker Masterpact MTZ3 circuit-breaker Masterpact MTZ1 circuit-breaker |
| Voltage release type | Closing coil |

Complementary

| | |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Control type | Standard |
| [Un] voltage power supply | 277 V AC 50/60 Hz |
| Threshold tripping voltage | 0.85...1.1 Un on closing |
| Holding power consumption | 4.5 VA |
| Circuit breaker mounting mode | Fixed |
| Maximum response time | 65 ms on closing for Masterpact MTZ1 80 ms on closing for Masterpact MTZ2 90 ms on closing for Masterpact MTZ3 |

Offer Sustainability

| | |
|----------------------------|-----------------------------------------------------------------------------------|
| Sustainable offer status | Green Premium product |
| REACH Regulation | <input checked="" type="checkbox"/> REACH Declaration |
| EU RoHS Directive | Compliant <input checked="" type="checkbox"/> EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | <input checked="" type="checkbox"/> Yes |
| China RoHS Regulation | <input checked="" type="checkbox"/> China RoHS Declaration |
| Environmental Disclosure | <input checked="" type="checkbox"/> Product Environmental Profile |
| Circularity Profile | <input checked="" type="checkbox"/> End Of Life Information |