
## LV847412

XF closing voltage release, diagnostics and communicating, Masterpact MTZ1 drawout, 24 VAC 50/60 Hz, 24/30 VDC





Main	
Range	Masterpact
Device short name	XF diag & com
Product or component type	Voltage release
Device application	Control
Range compatibility	Masterpact MTZ1 circuit-breaker
Voltage release type	Closing coil

Complementary

Control type	Communicating	
Signalling function	Electrical push-button activated	
	Coil powered	
	Error	
	Ready to close or open	
[Un] voltage power supply	2430 V DC	
	24 V AC 50/60 Hz	
Threshold tripping voltage	0.851.1 Un on closing	
Holding power consumption	4.5 W	
Circuit breaker mounting mode	Drawout	
Maximum response time	65 ms on closing for Masterpact MTZ1	

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	1.167 kg	
Package 1 Height	9 cm	
Package 1 width	6 cm	
Package 1 Length	4 cm	

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
Circularity Profile	End Of Life Information	