


Product data sheet

Characteristics

33664

MX shunt release, ComPact NS630b to NS3200 fixed, MasterPact NT/NW, rated voltage 380/480 VAC 50/60 Hz



Main

Device short name	MX
Product or component type	Voltage release
Device application	Control
Range compatibility	MasterPact NT Masterpact NW ComPact NS630b...1600 ComPact NS1600b...3200
Voltage release type	Shunt trip release
[Uc] control circuit voltage	380...480 V AC 50/60 Hz

Complementary

Threshold tripping voltage	0.7...1.1 x Un
Supply holding power	4.5 VA
Mounting mode	Fixed
Response time	50 ms (Compact NS630b...1600) 50 ms (Compact NS1600b...3200) 55 ms (Masterpact NT) 70 ms (Masterpact NW)
Accessory / separate part category	Spare parts for Masterpact NT Spare parts for Masterpact NW Spare parts for Compact NS1600b...3200 Spare parts for Compact NS630b...1600

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	150 g
Package 1 Height	3.5 cm
Package 1 width	8.2 cm
Package 1 Length	6.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.565 kg
Package 2 Height	13 cm
Package 2 width	9 cm
Package 2 Length	18 cm
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Weight	19.267 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

REACH Regulation	 REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------
