## Product data sheet Characteristics

## GVAU385

# Undervoltage release (MN), TeSys GV2-GV3, 380-400V AC 50Hz / 440V AC 60Hz





#### Main

| ase |
|-----|
|     |

#### Complementary

| Bases and Chillian              | OVOME  |
|---------------------------------|--|
| Range compatibility             | GV2ME  |
|                                 | GV2LE<br>GV2L  |
|                                 | GV2P   |
|                                 | GV3L   |
|                                 | GV3P   |
| [Uc] control circuit voltage    | 380400 V AC 50 Hz  |
| [os] control official voltage   | 440 V AC 60 Hz   |
| Control circuit voltage limits  | 0.851.1 Un   |
| [Ui] rated insulation voltage   | 690 V AC conforming to IEC 60947-1   |
| [-,                             | 600 V AC conforming to UL 60947-4-1  |
|                                 | 600 V AC conforming to CSA C22.2 No 60947-4-1  |
| Threshold tripping voltage      | 0.70.35 Un   |
| Inrush power in VA              | 12 VA AC   |
| Inrush power in W               | 8 W  |
| Hold-in power consumption in VA | 3.5 VA AC  |
| Hold-in power consumption in W  | 1.1 W  |
| Operating time                  | 1015 ms conforming to IEC 60947-1  |
| On-load factor                  | 100 %  |
| Connections - terminals         | Screw clamp terminals 1 cable(s) 12.5 mm²solid   |
|                                 | Screw clamp terminals 2 cable(s) 12.5 mm²solid   |
|                                 | Screw clamp terminals 1 cable(s) 0.752.5 mm²flexible without cable end<br>Screw clamp terminals 2 cable(s) 0.752.5 mm²flexible without cable end |
|                                 | Screw clamp terminals 2 cable(s) 0.752.5 mm-flexible without cable end Screw clamp terminals 1 cable(s) 0.751.5 mm²flexible with cable end       |
|                                 | Screw clamp terminals 1 cable(s) 0.751.5 mm flexible with cable end  |
| Tightening torque               | < 1.4 N.m on screw clamp terminals   |
| Mechanical durability           | 10000 Cycles with GV3P and GV3L  |
| ,,                              | 30000 cycles with GV2ME and GV2P   |
| Quantity per set                | Set of 10  |
| Height                          | 89 mm  |
| Width                           | 18 mm  |
| Depth                           | 66 mm  |
| Net weight                      | 0.105 kg   |
|                                 |  |

## Packing Units

| Unit Type of Package 1       | PCE    |  |
|------------------------------|--------|--|
| Number of Units in Package 1 | 1      |  |
| Package 1 Weight             | 115 g  |  |
| Package 1 Height             | 3.5 cm |  |
| Package 1 width              | 8.3 cm |  |
| Package 1 Length             | 9.1 cm |  |

#### Offer Sustainability

| Sustainable offer status   | Green Premium product   |
|----------------------------|---|
| REACh Regulation           | ☑ REACh Declaration   |
| REACh free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant EEU RoHS Declaration  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | ₫Yes  |
| China RoHS Regulation      | ☑ China RoHS Declaration  |
| Environmental Disclosure   | Product Environmental Profile   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

### Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|----------|-----------|

GVAU•••

