GVAX225

Undervoltage release (MN), TeSys GV2, 220-240 V AC 50 Hz, safety device for use with GV2ME





Main

Mairi		
Range	TeSys	
Device short name	GVAX	
Product or component type	Safety undervoltage trip	

Complementary

o impromornary	
Range compatibility	GV2ME
[Uc] control circuit voltage	220240 V AC 50 Hz
Control circuit voltage limits	0.851.1 Un
[Ui] rated insulation voltage	690 V AC conforming to IEC 60947-1 600 V AC conforming to UL 60947-4-1 600 V AC conforming to CSA C22.2 No 60947-4-1
Threshold tripping voltage	0.70.35 Un
Inrush power in VA	12 VA AC
Inrush power in W	8 W
Hold-in power consumption in VA	3.5 VA AC
Hold-in power consumption in W	1.1 W
Operating time	1015 ms conforming to IEC 60947-1
On-load factor	100 %
Connections - terminals	Screw clamp terminals 1 cable(s) 12.5 mm²solid Screw clamp terminals 2 cable(s) 12.5 mm²solid Screw clamp terminals 1 cable(s) 0.752.5 mm²flexible without cable end Screw clamp terminals 2 cable(s) 0.752.5 mm²flexible without cable end Screw clamp terminals 1 cable(s) 0.751.5 mm²flexible with cable end Screw clamp terminals 2 cable(s) 0.751.5 mm²flexible with cable end
Tightening torque	< 1.4 N.m on screw clamp terminals
Mechanical durability	30000 cycles
Quantity per set	Set of 10
Height	89 mm
Width	18 mm
Depth	66 mm
Net weight	0.105 kg

Packing Units

DOE	
PUE	
1	
131 g	
3.5 cm	
8.5 cm	
9.2 cm	
	3.5 cm 8.5 cm

Unit Type of Package 2	S01	
Number of Units in Package 2	16	
Package 2 Weight	2.256 kg	
Package 2 Height	15 cm	
Package 2 width	15 cm	
Package 2 Length	40 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

	•	
Warranty	18 months	

GVAX •••

