



Main

Device short name	MX
Product or component type	Voltage release
Device application	Control
Range compatibility	PowerPact B ComPact NSXm
Voltage release type	Shunt trip release
[Uc] control circuit voltage	24 V AC 50/60 Hz 24 V DC

Complementary

Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Threshold tripping voltage	0.7 Un opening
Mounting mode	Clip-on
Response time	< 50 ms
Auxiliary connection terminal	Spring

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	36 g
Package 1 Height	1.5 cm
Package 1 width	5.7 cm
Package 1 Length	6.3 cm
Unit Type of Package 2	S03
Number of Units in Package 2	120
Package 2 Weight	8.5 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins