



### Main

Range of product	Acti 9
Product or component type	Undervoltage release
Device short name	IMN
[Uc] control circuit voltage	115 V AC 400 Hz
Control type	Standard
9 mm pitches	2

### Complementary

Range compatibility	Acti 9 iC65 Acti 9 ARA Acti 9 iDPN Vigi Acti 9 iID Acti 9 iSW-NA Acti 9 RCA Acti 9 iDPN (China version) Acti 9 iC60 double terminals miniature circuit breaker Acti 9 iC40
Local signalling	Action indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Width	18 mm
Colour	White
Connections - terminals	Clamp terminal - 1 cable(s) 7 mm <sup>2</sup> - rigid Clamp terminal - 2 cable(s) 2.6 mm <sup>2</sup> - rigid Clamp terminal - 1 cable(s) 5 mm <sup>2</sup> - flexible Clamp terminal - 2 cable(s) 2.6 mm <sup>2</sup> - flexible with cable end
Tightening torque	1 N.m

### Environment

Standards	EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-25...50 °C
Ambient air temperature for storage	-40...85 °C

### Packing Units

Package 1 Weight	0.079 kg
Package 1 Height	0.300 dm
Package 1 width	0.810 dm
Package 1 Length	0.930 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------