



### Main

Range of product	Acti 9
Product name	Acti 9 STD
Product or component type	Remote control dimmer
Device short name	STD

### Complementary

Device application	Building
Load type	230 V AC halogen lamp: 60...1000 W 230 V AC incandescent lamp: 60...1000 W Low voltage halogen lamp with conventional transformer: 60...1000 W Motor: 60...600 W
Control type	Local control: push-button Remote control: push-button
Power consumption in VA	0.8 VA
Thermal losses	3 W
Input type	Push-button
[Ue] rated operational voltage	230 V AC +/- 10 % at 50 Hz
Protection type	Electronic over temperature protection Electronic overvoltage protection Single shot thermal fuse Electronic overload protection
Mounting support	DIN rail
9 mm pitches	8
Connected auxiliaries	Maximum 25 auxiliary push-buttons without light indication, distance : < 50 m Maximum 5 auxiliary push-buttons with light indication, distance : < 50 m
Connections - terminals	Screw terminals, 2 cable(s) 4 mm² top
Height	85 mm
Width	72 mm
Depth	62 mm
Net weight	120 g

### Environment

IP degree of protection	IP20
Standards	EN 60669-2-1
Directives	73/23/EEC - low voltage directive 89/336/EEC - electromagnetic compatibility
Ambient air temperature for operation	0...70 °C
Ambient air temperature for storage	0...60 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	187 g
Package 1 Height	8 cm
Package 1 width	9.7 cm
Package 1 Length	9.7 cm
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Weight	4.99 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	<input checked="" type="checkbox"/> End Of Life Information

## Contractual warranty

Warranty	18 months
----------	-----------