



Main

Range of product	Acti 9
Product name	Acti 9 STD
Product or component type	Remote control dimmer
Device short name	STD

Complementary

Device application	Building
Load type	230 V AC halogen lamp: 60...1000 W 230 V AC incandescent lamp: 60...1000 W Low voltage halogen lamp with conventional transformer: 60...1000 W Motor: 60...600 W
Control type	Local control: push-button Remote control: push-button
Power consumption in VA	0.8 VA
Thermal losses	3 W
Input type	Push-button 4 allows control up to 20 dimmers
[Ue] rated operational voltage	230 V AC +/- 10 % at 50 Hz
Input voltage	12...30 V AC/DC
Protection type	Electronic over temperature protection Single shot thermal fuse Electronic overvoltage protection Electronic overload protection
Mounting support	DIN rail
9 mm pitches	8
Connected auxiliaries	Maximum 25 auxiliary push-buttons without light indication, distance : < 50 m Maximum 5 auxiliary push-buttons with light indication, distance : < 50 m
Connections - terminals	Screw terminals, 2 cable(s) 4 mm ² top Screw terminals, 5 cable(s) 2.5 mm ² bottom
Maximum cable distance between devices	50 m
Height	85 mm
Width	72 mm
Depth	62 mm
Net weight	130 g

Environment

IP degree of protection	IP20
Standards	EN 60669-2-1
Directives	73/23/EEC - low voltage directive 89/336/EEC - electromagnetic compatibility
Ambient air temperature for operation	0...70 °C
Ambient air temperature for storage	0...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	199 g
Package 1 Height	8 cm
Package 1 width	9.7 cm
Package 1 Length	9.7 cm
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Weight	6.045 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------