



Main

Range of product	Acti 9
Product name	Acti 9 SCU
Product or component type	Remote control dimmer
Device short name	SCU

Complementary

Device application	Building
Load type	50 x fluocompact lamp, electronic ballast: ≤ 1500 W 12 x dual mounted fluorescent tube, electronic ballast: 58 W 20 x dual mounted fluorescent tube, electronic ballast: 36 W 25 x fluorescent tube, electronic ballast: 58 W 40 x dual mounted fluorescent tube, electronic ballast: 18 W 40 x fluorescent tube, electronic ballast: 36 W 50 x fluorescent tube, electronic ballast: 18 W
Control type	Local control: push-button Remote control: push-button
Power consumption in VA	0.8 VA
Thermal losses	3 W
[Ue] rated operational voltage	230 V AC +/- 10 % at 50 Hz
Output current	0.2...100 mA
Protection type	Electronic overvoltage protection Electronic over temperature protection Single shot thermal fuse Electronic overload protection
Mounting support	DIN rail
9 mm pitches	8
Connected auxiliaries	Maximum 25 auxiliary push-buttons without light indication, distance : < 50 m Maximum 5 auxiliary push-buttons with light indication, distance : < 50 m
Connections - terminals	Screw terminals, 2 cable(s) 4 mm ² top
Height	85 mm
Width	72 mm
Depth	62 mm
Net weight	130 g

Environment

IP degree of protection	IP20
Standards	EN 60669-2-1
Directives	89/336/EEC - electromagnetic compatibility 73/23/EEC - low voltage directive
Ambient air temperature for operation	0...70 °C
Ambient air temperature for storage	0...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	186 g
Package 1 Height	8 cm
Package 1 width	9.5 cm
Package 1 Length	9.5 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	24
Package 2 Weight	4.71 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------