



Main

Product or component type	Motor choke
Range compatibility	Altivar 71Q Altivar 61Q Altivar 61 Altivar 71
Product specific application	Output filter
[In] rated current	314 A
Product compatibility	ATV61HC11N4 ATV61HC13N4 ATV61HC20Y ATV61HC25Y ATV61HD55M3X ATV61HD75M3X ATV61QC13N4 ATV61QC16N4 ATV61QC16Y ATV61QC20Y ATV71HC11N4 ATV71HC13N4 ATV71HC16Y ATV71HC20Y ATV71HD55M3X ATV71HD75M3X ATV71QC11N4 ATV71QC13N4 ATV71QC13Y ATV71QC16Y
Needed quantity	3
Electrical connection	Tag connector M10

Complementary

Maximum motor cable length	150 M shielded cable P motor 55...75 kW at 200...240 V 1 300 M unshielded cable P motor 55...75 kW at 200...240 V 1 150 M shielded cable P motor 110...132 kW at 380...480 V 1 250 M unshielded cable P motor 110...132 kW at 380...480 V 1 150 M shielded cable P motor 160...250 kW at 500...690 V 1 250 M unshielded cable P motor 160...250 kW at 500...690 V 1 250 M shielded cable P motor 160...250 kW at 500...690 V 2 400 m unshielded cable P motor 160...250 kW at 500...690 V 2
DV/dt	500 V/μs max at 400 V 750 V/μs max at 500 V 1000 V/μs max at 690 V
Thermal losses	475 W
Maximum drive output frequency	100 Hz
Ambient air temperature for operation	-10...50 °C
Net weight	32 kg

Environment

IP degree of protection	IP20 (with kits VW3A9612,613) IP00
Ambient air temperature for storage	-25...70 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Package 1 Weight	38.000 kg
Package 1 Height	5.000 dm
Package 1 width	4.100 dm
Package 1 Length	5.930 dm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------