



Main

Product or component type	Ferrite suppressors for downstream contactor opening
Range compatibility	Altivar 312 Altivar 312 Solar Altivar 12
Product specific application	Output filter
Compatibility with variable speed drives	Variable speed drive ATV12H at 0.37 kW, 200...240 V, single phase Variable speed drive ATV12H at 0.18 kW, 200...240 V, three phase Variable speed drive ATV12H at 0.37 kW, 200...240 V, three phase Variable speed drive ATV312 at 0.37 kW, 200...240 V, single phase Variable speed drive ATV312 at 0.18 kW, 200...240 V, three phase Variable speed drive ATV312 at 0.37 kW, 200...240 V, three phase
Sale per indivisible quantity	3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	181 g
Package 1 Height	7 cm
Package 1 width	17 cm
Package 1 Length	24 cm
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Weight	1.802 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	56
Package 3 Weight	22.916 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------