



Main

Product or component type	Additional output module
Range compatibility	Altivar Machine ATV340 Easy Altivar 610 Altivar Process ATV900 Altivar Process ATV600
Input/output type	3 relay output
Discrete output number	3
Discrete output type	(R4, R5, R6) relay normally open, sampling time: 1 ms

Complementary

Electrical durability	100000 cycles
Minimum switching current	5 mA at 24 V DC
Maximum switching current	2 A at 250 V AC on inductive load, $\cos \phi = 0.4$ and $L/R = 5$ ms 2 A at 30 V DC on inductive load, $\cos \phi = 0.4$ and $L/R = 5$ ms 5 A at 250 V AC on resistive load, $\cos \phi = 1$ and $L/R = 5$ ms 5 A at 30 V DC on resistive load, $\cos \phi = 1$ and $L/R = 5$ ms
Electrical connection	Screw terminal block, 1.5 mm ² / AWG 16, 0.5 N.m
Net weight	0.4 kg

Packing Units

Package 1 Weight	0.138 kg
Package 1 Height	0.650 dm
Package 1 width	1.300 dm
Package 1 Length	1.900 dm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration