




Main

Range of product	Altivar Lexium
Product or component type	EMC input filter
Range compatibility	Lexium 32 Lexium 52 Lexium 28 Altivar Machine ATV340
Product compatibility	LXM28A LXM32, three-phase, line current 14.6...18.1 A Variable speed drive ATV340 at 2.2 kW, 380...480 V Variable speed drive ATV340 at 3 kW, 380...480 V Variable speed drive ATV340 at 4 kW, 380...480 V Variable speed drive ATV340 at 5.5 kW, 380...480 V Variable speed drive ATV340 at 7.5 kW, 380...480 V
Product specific application	Radio interference input filter
Mounting location	At variable speed drive side
Network number of phases	Three phase

Complementary

Maximum cable distance between devices	20 M conforming to IEC 61800-3 category C1 50 M conforming to IEC 61800-3 category C2 100 m conforming to IEC 61800-3 category C3
[In] rated current	25 A
Thermal losses	15.8 W
Network rated voltage	380...500 V
Tolerance	- 15...10 %
Net weight	1.35 kg
Emc filter compatibility	Type 023

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.494 kg
Package 1 Height	6.2 cm
Package 1 width	29.6 cm
Package 1 Length	22.4 cm
Unit Type of Package 2	S04
Number of Units in Package 2	11
Package 2 Weight	17.091 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P06
Number of Units in Package 3	44
Package 3 Weight	80.08 kg
Package 3 Height	77 cm
Package 3 width	60 cm
Package 3 Length	80 cm


Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Additional EMC Input Filters



Dimensions in mm


a	b	c	G	H	Ø
140	235	50	120	215	4.5

Dimensions in in.


a	b	c	G	H	Ø
5.51	9.25	1.96	4.72	8.46	0.18

Mounting Recommendations

Mounting the Filter on the Side of the Drive



Recommended Schema



- (1) Filter
- (2) Drive