



Main

Range	Masterpact
Product or component type	Application
Application description	ERMS
Range compatibility	Masterpact MTZ1 circuit breaker Masterpact MTZ2 circuit breaker Masterpact MTZ3 circuit breaker
Service description	ERMS function can be engaged/disengaged via Masterpact MTZ mobile app Micrologic X HMI backlight is blue when ERMS is engaged Reduction allows to trip faster when an internal arc fault occurs ERMS function is used to reduce the LSIG protection settings
Service benefits	ERMS function complies with NFPA 70E regulations ERMS engaged status visible at a distance thanks to Micrologic X blue backlight ERMS function decreases the amount of energy generated by an internal arc fault ERMS can be engaged/disengaged with your personal smartphone
Energy management	Diagnostics and maintenance (option)
Function of module	Protection

Complementary

Protection type	ERMS (option)
Software name	EcoStruxure Power Device

Packing Units

Package 1 Weight	0.010 kg
Package 1 Height	0.030 dm
Package 1 width	0.020 dm
Package 1 Length	0.030 dm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.