



Main

Range	Masterpact
Device short name	VPS
Product or component type	Power supply
Device application	High power distribution
Range compatibility	Masterpact MTZ2 circuit breaker Masterpact MTZ3 circuit breaker Masterpact MTZ1 circuit breaker
Mounting mode	Fixed
Product destination	Inside of the front panel control unit
Trip unit name	Micrologic

Complementary

Overvoltage category	IV
[Us] rated supply voltage	600 V AC 50...60 Hz tolerance: + 10 % - 15 %
Output voltage	24 V DC +/- 8 %
Power consumption in W	2.6 W 1.7 W
Network number of phases	Phase to phase Three phase
Height	22 mm
Width	45 mm
Depth	65 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	61 g
Package 1 Height	4.5 cm
Package 1 width	6 cm
Package 1 Length	8.2 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	532 g
Package 2 Height	13 cm
Package 2 width	9 cm
Package 2 Length	19 cm
Unit Type of Package 3	S02
Number of Units in Package 3	48
Package 3 Weight	3.444 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration