



Main

Range	PowerLogic
Product or component type	Current transducer
Accessory / separate part category	Measurement accessory
Range compatibility	Acti 9 iEM3000 iEM3555 Acti 9 iEM3000 iEM3565 PowerLogic EM4200 EM4235 PowerLogic EM4200 EM4236 PowerLogic EM3500 EM3502A PowerLogic EM3500 EM3550A PowerLogic EM3500 EM3555A PowerLogic EM3500 EM3560A PowerLogic EM3500 EM3561A
Current transformer type	Flexible core

Complementary

Electrical connection	Flying lead: 2.4 m600 V
Measurement current	50...5000 A
Network frequency	50 Hz
Frequency measurement range	50...1500 Hz
Measurement accuracy	1 %
Installation category	IV
Pollution degree	2
Thickness	8 mm
Height	300 mm opened:
Diameter	Closed: 96 mm

Environment

IP degree of protection	IP67
Standards	EN 61010-2-032 UL 61010-2-032 UL 61010-1 EN 61010-1 ANSI/IEEE C57.13
Product certifications	UL recognized CE CURus
Relative humidity	0...95 %
Ambient air temperature for operation	-15...60 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Package 1 Weight	150.450 g
Package 1 Height	300.000 mm
Package 1 width	300.000 mm
Package 1 Length	399.000 mm

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins