



## Main

|                           |                     |
|---------------------------|---------------------|
| Range                     | PowerLogic          |
| Product name              | CT                  |
| Product or component type | Current transformer |
| Secondary current         | 5 A                 |
| Accuracy class            | Class 0.5 at 60 VA  |
| [In] rated current        | 5000 A              |

## Complementary

|                                             |                                  |
|---------------------------------------------|----------------------------------|
| Current transformer type                    | Tropicalised for busbar          |
| Current transformer ratio                   | 5000/5                           |
| [Ith] conventional free air thermal current | 60 kA                            |
| Dynamic withstand current                   | 2.5 Ith                          |
| Maximum safety factor                       | 10                               |
| [Ue] rated operational voltage              | < 720 V AC 50/60 Hz              |
| [Ui] rated insulation voltage               | 3 kV                             |
| Mounting mode                               | Insulated locking screw          |
| Mounting support                            | Busbar                           |
| Width                                       | 175 Mm outside:<br>55 mm inner:  |
| Height                                      | 242 Mm outside:<br>165 mm inner: |
| Depth                                       | 110 mm total:                    |
| Net weight                                  | 3.1 kg                           |
| [Uimp] rated impulse withstand voltage      | 3 kV                             |
| Electrical insulation class                 | Class B                          |
| Opening of bars                             | 165 x 55                         |

|                              |          |
|------------------------------|----------|
| Package 1 Length             | 30 cm    |
| Unit Type of Package 2       | S03      |
| Number of Units in Package 2 | 2        |
| Package 2 Weight             | 8.641 kg |
| Package 2 Height             | 30 cm    |
| Package 2 width              | 30 cm    |
| Package 2 Length             | 40 cm    |

## Offer Sustainability

|                          |                                                                                                                             |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive        | Compliant <a href="#">EU RoHS Declaration</a>                                                                               |
| China RoHS Regulation    | <a href="#">China RoHS Declaration</a>                                                                                      |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile      | <a href="#">End Of Life Information</a>                                                                                     |
| WEEE                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |