26923

Auxiliary contact, Multi9, 1C/O, 1A to 6A, 220VAC to 415VAC, 24VDC to 130VDC, top connection, for RCCB only



Main Range of product Multi9 Product or component type Device short name OFS Signal contacts 1 C/O composition [In] rated current AC-12 3 A at 380...415 V, AC 50/60 Hz AC-12 6 A at 220...240 V, AC 50/60 Hz

DC-12 1 A at 130 V, DC DC-12 1.5 A at 60 V, DC DC-12 2 A at 48 V, DC DC-12 6 A at 24 V, DC

9 mm pitches 1

Complementary

Mounting mode	Fixed	
Mounting support	DIN rail	
Comb busbar and distribution block compatibility	Top: YES	
Height	84 mm	
Width	9 mm	
Depth	73 mm	
Connections - terminals	Clamp terminal2 cable(s) 1.5 mm² - flexible Clamp terminal2 cable(s) 1.5 mm² - rigid Clamp terminal1 cable(s) 0.52.5 mm² - flexible Clamp terminal1 cable(s) 0.52.5 mm² - rigid	
Wire stripping length	9 mm	
Tightening torque	1 N.m	

Environment

Standards	EN/IEC 60947-5-1 EN 62019-2
Product certifications	NEMKO[RETURN]DEMKO[RETURN]SEMKO[RETURN]CEBEC[RETURN]FIMKO
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 conforming to EN/IEC 60947-5-1
Tropicalisation	2 conforming to EN/IEC 60947-5-1
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-2550 °C
Ambient air temperature for storage	-4085 °C

Packing Units

PCE	
1	
8 cm	
2 cm	
9.5 cm	
43 g	
BB1	
12	
	1 8 cm 2 cm 9.5 cm 43 g BB1

Package 2 Height	9 cm
Package 2 Width	10 cm
Package 2 Length	25.5 cm
Package 2 Weight	584 g
Unit Type of Package 3	S03
Number of Units in Package 3	108
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	5.694 kg

Offer Sustainability

Compliant EPEU RoHS Declaration
Yes
Yes
China RoHS Declaration
₫Yes
No need of specific recycling operations
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months	
--------------------	--