Product data sheet Characteristics

3240203000

Current Transducer: Split Core, H921-S6, 30 mA (Max.) at 12 to 30 VDC, 0 to 30/60/120 A (selectable), 4 to 20mAdc

Range of product	HX21 Series		
Product or component type	Sensor		
Sensor model	H921-S6		
Type of measurement	AC current		
Device application	Building automation systems		
Current measurement accuracy	+/- 2 % of full scale above 10 % of selected range		
Current measurement range	030 A 060 A 0120 A		
Sensor type	Current transducer, AC		
AWG gauge	AWG 24AWG 14		
Network frequency	5060 Hz		
Opening width	21 mm		
Mounting support	Split core housing		
Relative humidity	1090 % RH, non-condensing		
Ambient air temperature for operation	-1560 °C		
Analogue output type	420 mA		
Output type	Analog		
Product certifications	UL[RETURN]CE		
Targeted region	Europe Asia Pacific.		

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.9 cm	
Package 1 Width	8.0 cm	
Package 1 Length	9.6 cm	
Package 1 Weight	181.4 g	

Offer Sustainability

Circularity Profile	No need of specific recycling operations		
Environmental Disclosure	Product Environmental Profile		
EU RoHS Directive	Compliant E EU RoHS Declaration	Compliant EEU RoHS Declaration	