

Product data sheet

Characteristics

7211736000

Venta V211T Globe Valve, 2-Way, PN16, Rp 1
1/4 Internal thread, DN32, 16 Kvs, Nodular Iron
Body and Seat, Brass Plug, Max Glycol 50%.



Main

Valve product range	Venta
Product or component type	Valve
Valve type	Globe
Valve product series	V211T
Valve model	V211T/32/16
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	2-Way
Valve connection type	Rp Internal
Valve connection size	Rp 1-1/4
Body size	32 mm (1-1/4 in)
Pipe size	32 mm
Flow characteristic	Equal percentage
Flow coefficient	18.5 cv 16 kvs
Pressure class	PN16
Operating fluid temperature	-20...120 °C
Pressure fluid max delta P normal life	399.90 kPa
Control valve rangeability	Greater than 50:1
Stroke length	20 mm
Seat leakage	Port A: Class IV-S1 (0.005 %)
Stem flow action	Stem up closed
Stem movement	Linear
Trim material	Brass
Body material	Nodular cast iron EN-JS 1030
Seat material	Port A: nodular cast iron EN-JS 1030
Stem material	Stainless steel AISI 303
Plug material	CW602N brass
Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A:EPDM (ethylene propylene diene monomer)
Packing material	EPDM (ethylene propylene diene monomer)
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	13.5 cm
Package 1 Length	18.0 cm
Package 1 Weight	1.663 kg

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations