Product data sheet Characteristics

7213246000

Venta V232 Globe Valve, 2-Way, PN25, Flanged, Balanced Plug, DN40, Kvs 25, Nodular Iron body, Stainless Steel Plug and Seat, Max Glycol 50%.



Main	
Valve product range	Venta
Product or component type	Valve
Valve type	Globe
Valve product series	V232
Valve model	V232/40/25
Medium compatibility	Water Glycol 25 % Glycol 30 % Glycol 50 % Steam
Valve configuration	2-Way
Valve connection type	Flanged
Valve connection size	DN40 (ISO 7005-2)
Body size	40 mm (1-1/2 in)
Pipe size	40 mm
Flow characteristic	Equal percentage
Flow coefficient	28.91 cv 25 kvs
Pressure class	PN25
Operating fluid temperature	-20150 °C
Pressure fluid max delta P normal life	799.79 kPa
Saturated steam temperature	-20150 °C
Control valve rangeability	Greater than 200:1
Stroke length	20 mm
Seat leakage	Port A: Less than 0.02 % of kvs
Stem flow action	Stem up closed
Trim material	Stainless steel
Body material	Nodular cast iron EN-JS 1025
Seat material	Port A: stainless steel AISI 303
Stem material	Stainless steel AISI 303
Plug material	Stainless steel AISI 303
Stem seal material	EPDM (ethylene propylene diene monomer)
Seating seal material	Port A:metal to metal
Packing material	EPDM (ethylene propylene diene monomer)
Targeted region	Europe Asia Pacific.

Australia.

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	15.0 cm	
Package 1 Width	20.5 cm	
Package 1 Length	25.0 cm	
Package 1 Weight	9.35 kg	

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	