



Main

Product or component type	Valve
Valve type	Globe
Valve product series	V292
Valve model	V292/150/350
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	2-Way
Valve connection type	Flanged
Valve connection size	DN150 (ISO 7005-2)
Body size	50 mm (2 in)
Pipe size	150 mm
Flow characteristic	Equal percentage
Flow coefficient	404.68 cv 350 kvs
Pressure class	PN25
Operating fluid temperature	-10...150 °C
Pressure fluid max delta P normal life	103.42 kPa
Control valve rangeability	Greater than 50:1
Stroke length	50 mm
Seat leakage	Port A: Less than 0.05 % of kvs
Stem flow action	Stem down closed
Trim material	Stainless steel
Body material	Nodular cast iron EN-JS 1025
Seat material	Port A: stainless steel AISI 420
Stem material	Stainless steel AISI 420
Plug material	Stainless steel AISI 420
Stem seal material	PTFE (polytetrafluoroethylene)
Seating seal material	Port A: metal to metal
Packing material	PTFE (polytetrafluoroethylene)
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	51.0 cm
Package 1 Width	29.0 cm
Package 1 Length	47.0 cm
Package 1 Weight	90.25 kg

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations