Product data sheet Characteristics

7311145000

Venta V311 Globe Valve, 3-Way, PN16, Flanged, DN50, 38 Kvs, Nodular Iron Body and Seat, Brass plug, Max. Glycol 50%, Stem Up Closed (A-AB).



Main Valve product range Venta Product or component Valve type Valve type Globe V311 Valve product series Valve model V311/50/38 Medium compatibility Glycol 25 % Water Glycol 30 % Glycol 50 % Valve configuration 3-Way Valve connection type Flanged Valve connection size DN50 (ISO 7005-2) Body size 50 mm (2 in) Pipe size 50 mm Flow characteristic Equal percentage Flow coefficient 43.94 cv 38 kvs Pressure class PN16 -20...120 °C Operating fluid temperature Pressure fluid max delta 399.90 kPa P normal life Control valve Greater than 50:1 rangeability Stroke length 20 mm Seat leakage Port A: Class IV-S1 (0.005 %) Stem flow action Stem up closes A and opens B to AB Stem movement Linear Trim material Brass Body material Nodular cast iron EN-JS 1030 Seat material Port A: nodular cast iron EN-JS 1030 Port B: nodular cast iron EN-JS 1030 Stainless steel AISI 303 Stem material CW602N brass Plug material Stem seal material EPDM (ethylene propylene diene monomer) Seating seal material Port A:EPDM (ethylene propylene diene monomer) Port B:EPDM (ethylene propylene diene monomer) Packing material EPDM (ethylene propylene diene monomer) Targeted region Europe

Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.5 cm
Package 1 Width	23.5 cm
Package 1 Length	28.5 cm
Package 1 Weight	10.35 kg

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	