



### Main

Range	Mureva
Product or component type	Socket-outlet
Device short name	Mureva socket
Plug, socket category	Low voltage
Poles description	2P + E
Network type	AC
Outlet standard	Domestic German

### Complementary

[In] rated current	16 A 10 A
Network frequency	50/60 Hz
[Ue] rated operational voltage	250 V
Plug, socket material	Housing: self-extinguishing engineering polymer
Contacts material	Pins: stainless steel Springs: stainless steel
Cover type	Lid
Device mounting	Surface
Mounting mode	Panel-mounted
Socket number	1
Connections - terminals	Captive screws
Net weight	0.112 kg
Base dimension	65 x 85 mm
Height	85 mm
Width	65 mm
Depth	45.2 mm
Colour	Grey (RAL 7035)

### Environment

Standards	IEC 60884
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 62262
Fire resistance	850 °C conforming to IEC 60695-2-1
Relative humidity	50 % at 40 °C 70 % at 30 °C 90 % at 20 °C
Ambient air temperature for operation	35 °C ( 86400 s ) -25...40 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.6 cm
Package 1 Width	6.5 cm
Package 1 Length	8.6 cm
Package 1 Weight	110 g
Unit Type of Package 2	BB1
Number of Units in Package 2	18
Package 2 Height	11.9 cm
Package 2 Width	26.2 cm
Package 2 Length	26.8 cm
Package 2 Weight	2.137 kg
Unit Type of Package 3	S03
Number of Units in Package 3	54
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	6.899 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------